

BATTERY STRAPPING TOOL FOR PLASTIC STRAP WITH FRICTION WELD



TECHNICAL SPECIFICATIONS

DIMENSIONS

Lenght	316 mm
Width	140 mm
Height	160 mm
Weight	4.1 Kgs

POWER SUPPLY

Battery	14.8V-4 A/h LI-PO
----------------	-------------------

PRESTAZIONI

Tension max force	600N / 3500N
Tensioning Speed	12mt/m
Sealing	Friction Welding
Joint Strenght	75% of breaking strenght*

* variable according to strap type



MODELS

CODE	TYPE	STRAP	THICKNESS
T209997-18V	ITI22 / 13 mm-16 mm With one battery	PP-PET 13 mm-16 mm	0.5 mm - 1.05 mm
T2099971-18V	ITI22 / 13 mm-16 mm With one battery + battery charger	PP-PET 13 mm-16 mm	0.5 mm - 1.05 mm
T2099972-18V	ITI22 / 13 mm-16 mm With two batteries + battery charger	PP-PET 13 mm-16 mm	0.5 mm - 1.05 mm
T2099973-18V	ITI22 / 13 mm-16 mm With three batteries + battery charger	PP-PET 13 mm-16 mm	0.5 mm - 1.05 mm
B800580-18V	BATTERY 18V -4,0 A/h for latest release tool	PP-PET 13 mm-16 mm	0.5 mm - 1.05 mm
B800581-18V	Charger for 18V battery for latest release tool	PP-PET 13 mm-16 mm	0.5 mm - 1.05 mm
77B800509	BATTERY 18V -4,0 A/h - 3.0Ah	PP-PET 13 mm-16 mm	0.5 mm - 1.05 mm
77B800508	Charger for 14.4V battery	PP-PET 13 mm-16 mm	0.5 mm - 1.05 mm


EMBOSSED POLYESTER STRAP



SMOOTH POLYESTER STRAP



POLYPROPYLENE STRAP



ITIPACK s.r.l.

Via Capovilla, 73/bis - 36030 - VILLAVERLA (Vicenza) Italy
Phone. +39 0445 855 977 r.a. - Fax +39 0445 350034
e-mail : info@itipack.it - Web: www.itipack.com