



## BATTERY STRAPPING TOOL FOR POLYESTER STRAP WITH VIBRATION SEALING



TECHNICAL SPECIFICATIONS		MODEL			
DIMENSIONS		CODE	TYPE	STRAP	THICKNESS
Length	300 mm	77T259997	ITI25 / 16 mm-19 mm with one battery	PET 16 mm	0.8 mm ÷ 1.05 mm
Width	150 mm			5/8"	0.3" ÷ 4.1"
Height	160 mm	77T2599971	ITI25 / 16 mm-19 mm with one battery and charger	PET 19 mm	0.7 mm ÷ 1.3 mm
Weight	4,1 Kgs			3/4"	0.2" ÷ 0.5"
FEEDING		77T2599972	ITI25 / 16 mm-19 mm with two batteries and charger	PET 16 mm	0.8 mm ÷ 1.05 mm
Battery	14.8V-3.2 A/h LI-PO			5/8"	0.3" ÷ 4.1"
PERFORMANCE		77T2599972	ITI25 / 16 mm-19 mm with two batteries and charger	PET 19 mm	0.7 mm ÷ 1.3 mm
Max. tension force	5500N			3/4"	0.2" ÷ 0.5"
Tensioning speed	12mt/m	<b>EMBOSSED POLYESTER STRAP</b>			
Sealing	Vibration sealing				
Joint strength	75% of breaking strength*	<b>SMOOTH POLYESTER STRAP</b>			
* variable according to strap type					
OPERATING MODES		Fully Automatic			
		Semi Automatic			
		Manual			
With Fully Automatic Mode tensioning, welding and strap cutting are performed with only one push of a button.					

