

PNEUMATIC STEEL STRAPPING TOOL WITH SEAL JOINT



TECHNICAL SPECIFICATIONS

DIMENSION

Lenght	350 mm
Width	140 mm
Height	170 mm
Weight	4 kgs

POWER SUPPLY

Pressure range 5.5 -7 bar / 78 -99 psi

Air consumption 12 L/s – 25 cuft/min

PERFORMANCE

Max tension force	7500N -6 bar-87psi
Tensioning speed	12 mt/min (2000N) 5 mt/min (5500N) 4 mt/min (7500N)
Sealing	Seal double notch
Joint strenght	75% of breaking strenght*
Transmission value	-

* variable according to strap type

MODELS

CODE	TYPE	STRAP	THICKNESS
T401311	ITI40 -13 mm STEEL - 2000N SINGLE NOTCH	13 MM	0,4mm - 0,8mm (Regular duty) 0,4mm - 0,63mm (High Tensile)
T401321	ITI40 -13 mm STEEL - 5500N SINGLE NOTCH	13 MM	0,4mm - 0,8mm (Regular duty) 0,4mm - 0,63mm (High Tensile)
T401331	ITI40 -13 mm STEEL - 7500N SINGLE NOTCH	13 MM	0,4mm - 0,8mm (Regular duty) 0,4mm - 0,63mm (High Tensile)
T401611	ITI40 -16 mm STEEL - 2000N SINGLE NOTCH	16 MM	0,4mm - 0,8mm (Regular duty) 0,4mm - 0,63mm (High Tensile)
T401621	ITI40 -16 mm STEEL - 5500N SINGLE NOTCH	16 MM	0,4mm - 0,8mm (Regular duty) 0,4mm - 0,63mm (High Tensile)
T401631	ITI40 -16 mm STEEL - 7500N SINGLE NOTCH	16 MM	0,4mm - 0,8mm (Regular duty) 0,4mm - 0,63mm (High Tensile)
T401911	ITI40 -19 mm STEEL - 2000N SINGLE NOTCH	19 MM	0,4mm - 0,8mm (Regular duty) 0,4mm - 0,63mm (High Tensile)
T401921	ITI40 -19 mm STEEL - 5500N SINGLE NOTCH	19 MM	0,4mm - 0,8mm (Regular duty) 0,4mm - 0,63mm (High Tensile)
T401931	ITI40 -19 mm STEEL - 7500N SINGLE NOTCH	19 MM	0,4mm - 0,8mm (Regular duty) 0,4mm - 0,63mm (High Tensile)

SEAL SINGLE NOTCH



ITIPACK s.r.l.

Via Capovilla, 73/bis - 36030 - VILLAVERLA (Vicenza) Italy

Phone. +39 0445 855 977 r.a. - Fax +39 0445 350034

E-mail : info@itipack.it - Web: www.itipack.it