

PNEUMATIC STEEL STRAPPING TOOL WITH SEAL JOINT



TECHNICAL SPECIFICATIONS

DIMENSION

Length	430 mm
Width	260 mm
Height	310 mm
Weight	10.3 kgs

POWER SUPPLY

Pressure range	5.5 - 7 bar / 78 - 99 psi
Air consumption	12 L/s - 25 cuft/min

PERFORMANCE

Max tension force	9000N - 6.5bar-87psi
Tensioning speed	9000N - 15000N (6 bar - 87 psi)
Sealing	Seal double notch
Joint strenght	75% of breaking strenght*
Transmission value	-

* variable according to strap type

MODELS

CODE	TYPE	STRAP	THICKNESS
T411943	ITI41 - 19 mm - 9000N-3B	19mm	0.6 mm - 1 mm 0.63 mm - 0.8 mm
T412543	ITI41 - 25 mm - 15000N-3B	25mm	0.6 mm - 1 mm 0.63 mm - 0.8 mm
T413243	ITI41 - 25 mm - 15000N-3B	25mm	0.6mm - 1 mm 0.63 mm - 0.8 mm
T413249	ITI41 - 32 mm - 9000N-3B	32mm	0.6mm - 1 mm 0.63 mm - 0.8 mm

DOUBLE NOTCH SEAL JOINT



ITIPACK s.r.l.
Via Capovilla, 73/bis - 36030 - VILLAVERLA (Vicenza) Italy
Phone. +39 0445 855 977 r.a. - Fax +39 0445 350034
E-mail : info@itipack.it - Web: www.itipack.it