

## PNEUMATIC SEALER FOR STEEL STRAP 19MM / 25MM / 32MM



### TECHNICAL SPECIFICATIONS

#### DIMENSION

<b>Length</b>	430 mm
<b>Width</b>	260 mm
<b>Height</b>	310 mm
<b>Weight</b>	11,3 kgs

#### POWER SUPPLY

Pressure range	5.5 -7 bar / 78 -99 psi
Air consumption	12 L/s - 25 cuft/min

#### PERFORMANCE

Max tension force	9000N
Tensioning speed	N.A
Sealing	Seal double notch
Joint strenght	75% of breaking strenght*
Transmission value	-

\*Variable according to strap type

### MODELS

CODE	DESCRIPTION	STRAP	THICKNESS
T511943	ITA 51 - 19 mm Steel Strap 9000N 3B DOUBLE NOTCH	19 mm	0,6mm - 1,0mm (Regular duty) 0,63mm - 0,8mm (High Tensile)
T512543	ITA 51 - 25 mm Steel Strap 9000N 3B DOUBLE NOTCH	25 mm	0,6mm - 1,0mm (Regular duty) 0,63mm - 0,8mm (High Tensile)
T513243	ITA 51 - 32 mm Steel Strap 9000N 3B DOUBLE NOTCH	32 mm	0,6mm - 1,0mm (Regular duty) 0,63mm - 0,8mm (High Tensile)

#### SEAL DOUBLE NOTCH



ITIPACK s.r.l.  
Via Capovilla, 73/bis - 36030 - VILLAVERLA (Vicenza) Italy  
Phone. +39 0445 855 977 r.a. - Fax +39 0445 350034  
E-mail : info@itipack.it - Web: www.itipack.it