

## BATTERY STRAPPING TOOL FOR POLYESTER STRAP WITH VIBRATION SEALING



TECHNICAL SPECIFICATIONS	
DIMENSIONS	
Length	300 mm
Width	150 mm
Height	200 mm
Weight	6,4 Kgs
FEEDING	
Battery	36V-2.5 A/h LI-PO
PERFORMANCE	
Max. tension force	7000N
Tensioning speed	8mt/m
Sealing	Friction weld seal
Joint strength	75% of breaking strength*

\* variable according to strap type

OPERATING MODES	
Fully Automatic	
Semi Automatic / Manual	
Manual	

With Fully Automatic Mode tensioning, welding and strap cutting are performed with only one push of a button.



MODEL			
CODE	TYPE	STRAP	THICKNESS
77T279997	ITI27 / 19/25/32 mm 7000N equipped with one battery	PET 19/25/32 mm	25/32mm x 0,8 ÷ 1,3 mm 19mm x 1 ÷ 1,4 mm
77T2799971	ITI27 / 19/25/32 mm 7000N equipped with one battery and charger	PET 19/25/32 mm	25/32mm x 0,8 ÷ 1,3 mm 19mm x 1 ÷ 1,4 mm
77T2599972	ITI27 / 19/25/32 mm 7000N equipped with two batteries and charger	PET 19/25/32 mm	25/32mm x 0,8 ÷ 1,3 mm 19mm x 1 ÷ 1,4 mm
77B800477	Li-Ion Battery 36V 2,5 Ah for ITI27 (1,1kg)	PET 19/25/32 mm	25/32mm x 0,8 ÷ 1,3 mm 19mm x 1 ÷ 1,4 mm
77B800483	Battery Charger 230V for Li-Ion batteries	PET 19/25/32 mm	25/32mm x 0,8 ÷ 1,3 mm 19mm x 1 ÷ 1,4 mm

### EMBOSSED POLYESTER STRAP



### SMOOTH POLYESTER STRAP

